



AL BL

Extreme pressure white grease for incidental contact with foodstuffs

Description

On account of its technical characteristics, the AL BL grease is extremely resistant with respect to metals and has proven to be well adapted to humid environments; it is highly resistant to water and steam. AL BL is registered by NSF International, in category H1. This indicates that it is authorized for use in incidental contact with food. (N°138272)

Applications

Ideal for lubricating smooth bearings, pivots and bearings under high loads in the food processing industries (canning, baking, biscuit, dairy, meat, fish, fruit and vegetable industries or harvesting machinery for example)

Technical data

Operating temperature range: -20°C to +150°C

NLGI Grade: 1/2

Load: 400 kg

Reference	designation	Packaging				food certificate number
ALBL50	GREASE- NLGI1/2-FOOD GRADE-AL BL- KEG 50KG-WITH POUCH	TONNELET		KEG	50 KG	138272
ALBL5L	GREASE- NLGI1/2-FOOD GRADE-AL BL- BUCKET 5L	CARTON	2	BUCKET	5 L	138272
ALBLB1	GREASE- NLGI1/2-FOOD GRADE-AL BL-TIN 1L	CARTON	6	TIN	1 L	138272
ALBLFT	GREASE- NLGI1/2-FOOD GRADE-AL BL- DRUM 180KG	FUT		DRUM	180 KG	138272

