



## CENTRALES PMP

### PMP SERIES COMPACT ELECTRIC PUMPS

#### Description

These electric pumps are mainly intended for lubrication applications with progressive distributors, they can be used with oil or grease. The tanks are available in Plexiglas with capacities of 2, 4, 6 and 8 liters or in steel with capacities of 6, 8 and 12 litres. As an option, they can be fitted with a minimum level switch. Their number of outlets can range from 1 to 3. The nominal flow rate per outlet is adjustable from 0.8 to 3.8 cc/min. Each outlet can be individually equipped with a pressure relief valve with or without pressure gauge. The electro-pumps can be delivered with or without an electronic card for managing lubrication and pause times, controlling the minimum level of lubricant and possibly controlling the lubrication cycles if the progressive distributor installed at the outlet is fitted with a PNP cycle switch.

Reference	designation	Packaging				food certificate number
34-0X-1B-0X-301 10		CARTON	1		1 PC	
34-0X-1B-0X-241 10		CARTON	1		1 PC	
34-0X-1B-0X-201 10		CARTON	1		1 PC	
8501627		CARTON	1		1 PC	
9550479		CARTON	1		1 PC	
34-0X-1B-0X-341 10		CARTON	1		1 PC	
44-0X-1B-0X-201 10-						
44-0X-1B-0X-241 10						
44-0X-1B-0X-301 10						
44-0X-1B-0X-341 10						